

Mensagex 

Olá Carlos Junior

[alterar dados](#) | [alterar e-mail](#) | [alterar senha](#) |  [conectar Facebook](#)

E-MAIL FACEBOOK

INICIAL CONTATOS TEMPLATES ENVIOS RELATÓRIOS SUBCONTAS

Suporte técnico

Você não possui créditos no momento

[extrato de créditos](#)

[Comprar créditos](#)

PRIMEIROS PASSOS

1 IMPORTE SEUS E-MAILS

2 IMPORTE SEUS TEMPLATES

3 CRIE UM ENVIO

Mensagex



ONLINE E-MAIL MARKETING SYSTEM

Importe suas listas com seus e-mails através de um arquivo.

Envie ou crie o template (arte) que será enviada para seus clientes.

Crie uma campanha utilizando as templates importados.

Acompanhe em tempo real o resultado de suas campanhas enviadas.

MacBook Air

Authentication

Enter any string as your username and supply your API Key as the password. Your HTTP client library should have built-in support for Basic authentication.

HTTP Methods

The API supports 4 HTTP methods for interacting with resources:

- **GET** Make a GET request to retrieve data. GET requests will never cause an update or change to your data.
- **POST** Use a POST request to create new resources. For example, make a POST request to a collection endpoint (like /lists) where the body of your request JSON is a new list.
- **PUT** Use a PUT request to update a resource.
- **DELETE** Make a DELETE request to remove a resource.

Request response

We expose API response in standard HTTP response codes.

Success:

- HTTP/1.1 201 "ItemCreated": new item creation
- HTTP/1.1 202 "ExecutedRequest": requested action executed

Error:

- HTTP/1.1 406 "RequestError": Internal server error
- HTTP/1.1 401 "InvalidAPI": Invalid API key
- HTTP/1.1 402 "UnavailableResources": Insufficient credits

CONTACTS

SEARCH

REQUEST

Method	Path
GET	/contact

PARAMETER	TYPE	REQUIRED	DESCRIPTION
COUNT	Integer	No	The number of records to return
PAGE	Integer	No	The page number

```
curl -user <any-string>:<your-api-key> \
  --request GET
"https://mensagemex.com.br/api/contact?page=0&count=10"
```

RESPONSE

CONTACT ATTRIBUTES	Type	Description
ID	Integer	Contact's Identifier
NAME	Integer	Contact's name
EMAIL	Integer	Contact's e-mail

```
[{
  "email": "robert.herjavec@cnn.com",
  "id": 1779,
  "name": "Robert Herjavec "
}, {
  "email": "markcuban@broadcast.com",
  "id": 9365,
  "name": "Mark Cuban"
}]
```

GET

REQUEST

Method	Path
GET	/contact/{contact-id}

PARAMETERS	TYPE	REQUIRED	DESCRIPTION
COUNT	Integer	No	The number of records to return
PAGE	Integer	No	The page number

```
curl -user <any-string>:<your-api-key> \  
  --request GET "https://messagex.com.br/api/contact/1779"
```

RESPONSE

CONTACT ATTRIBUTES	Type	Description
ID	Integer	Contact's Identifier
NAME	Integer	Contact's name
EMAIL	Integer	Contact's e-mail
LISTS	List	List(s) that contact participates

LIST ATTRIBUTES	Type	Description
ID	Integer	List's Identifier
NAME	Integer	List's name

```
{  
  "email": " robert.herjavec@cnn.com",  
  "id": 1779,  
  "lists": [{  
    "id": 258,  
    "name": "Shark list"  
  }],  
  "name": "Robert Herjavec"  
}
```

INSERT

REQUEST

Method	Path
POST	/contact

CONTACT ATTRIBUTES	TYPE	REQUIRED	DESCRIPTION
NAME	Integer	No	Contact's name
EMAIL	Integer	Yes	Contact's e-mail
LISTS	List	Yes	List(s) that contact participates

LIST	ATTRIBUTES	Type	Required	Description
	ID	Integer	Yes	List's identifier

```
curl -user <any-string>:<your-api-key> \
  --request POST "https://mensagem.com.br/api/contact"
```

```
{
  "email": " robert.herjavec@cnn.com",
  "lists": [{
    "id": 258
  }],
  "name": "Robert Herjavec"
}
```

UPDATE

REQUEST

Method	Path
PUT	/contact/{contact-id}

CONTACT ATTRIBUTES	TYPE	REQUIRED	DESCRIPTION
NAME	Integer	No	Contact's name
EMAIL	Integer	No	Contact's e-mail
LISTS	List	No	List(s) that contact participates

LIST ATTRIBUTES	TYPE	REQUIRED	DESCRIPTION
ID	Integer	Yes	List's identifier

```
curl -user <any-string>:<your-api-key> \
  --request PUT "https://messaging.com.br/api/contact/1779"
```

```
{
  "email": " robert.herjavec@herjavec.com",
  "lists": [{
    "id": 258, "id": 300, "id": 301
  }]
}
```

DELETE

REQUEST

Method	Path
DELETE	/contact/{contact-id}

```
curl -user <any-string>:<your-api-key> \  
  --request DELETE "https://mensagex.com.br/api/contact/1779"
```


LISTS

SEARCH

REQUEST

Method	Path
GET	/list

PARAMETER	TYPE	REQUIRED	DESCRIPTION
COUNT	Integer	No	The number of records to return
PAGE	Integer	No	The page number

```
curl -user <any-string>:<your-api-key> \  
  --request GET "https://mensagemex.com.br/api/list?page=0&count=10"
```

RESPONSE

LIST ATTRIBUTES	Type	Description
ID	Integer	List's Identifier
NAME	Integer	List's name

```
[{  
  "id": 258,  
  "name": "Shark list"  
}, {  
  "id": 300,  
  "name": "CEOs"  
}]
```

TEMPLATES

SEARCH

REQUEST

Method	Path
GET	/template

PARAMETER	TYPE	REQUIRED	DESCRIPTION
COUNT	Integer	No	The number of records to return
PAGE	Integer	No	The page number

```
curl -user <any-string>:<your-api-key> \  
  --request GET  
  "https://mensagemex.com.br/api/template?page=0&count=10"
```

RESPONSE

ATTRIBUTES	Type	Description
ID	Integer	Template's Identifier
NAME	Integer	Template's name
URL	String	Template's URL

```
[{  
  "id": 5899,  
  "name": "50% discount",  
  "url": "  
http://www.mensagemex.com.br/templates/23221/5899/preview.html"  
}, {  
  "id": 7785,  
  "name": "Security information",  
  "url": "  
http://www.mensagemex.com.br/templates/23221/7785/preview.html"  
}]
```

CAMPAIGN

SEARCH

REQUEST

Method	Path
GET	/campaign

PARAMETER	TYPE	REQUIRED	DESCRIPTION
COUNT	Integer	No	The number of records to return
PAGE	Integer	No	The page number

```
curl -user <any-string>:<your-api-key> \
  --request GET
  "https://mensagem.com.br/api/campaign?page=0&count=10"
```

RESPONSE

CAMPAIGN ATTRIBUTES	Type	Description
DATE	Long	Campaign date in unix time
ID	Integer	Campaign's Identifier
NAME	String	Campaign's name
STATUS	String	Possible values: SCHEDULED, SENDING, PENDING, SENT.

```
[{
  "date": 1458177120,
  "id": 3895,
  "name": "Campaign April 2015",
  "status": "SCHEDULED",
}, {
  "date": 1455708063,
  "id": 3899,
  "name": "Discount Campaign",
  "status": "SENT",
}]
```

GET

REQUEST

Method	Path
GET	/campaign/{campaign-id}

PARAMETERS	TYPE	REQUIRED	DESCRIPTION
COUNT	Integer	No	The number of records to return
PAGE	Integer	No	The page number

```
curl -user <any-string>:<your-api-key> \
  --request GET "https://messagex.com.br/api/campaign/3895"
```

RESPONSE

CAMPAIGN ATTRIBUTES	Type	Description
DATE	Long	Sent date in unix time
ID	Integer	Campaign's Identifier
NAME	String	Campaign's name
STATUS	String	Possible values: SCHEDULED, SENDING, PENDING, SENT.
HTML	String	Url of campaign's template
LISTS	List	Campaign used lists
SENDEREMAIL	String	Campaign sender e-mail
SENDERNAME	String	Campaign sender name
SUBJECT	String	Campaign subject
SENT	Integer	Number of sent e-mails
UNIQUEOPENS	Integer	Number of opened (unique)
CLICKS	Integer	Number of clicks
UNIQUECLICKS	Integer	Number of clicks (unique)
BOUNCES	Integer	Number of bounced e-mails
HARDBOUNCES	Integer	Number of hard bounces
SOFTBOUNCES	Integer	Number of soft bounces
UNSUBSCRIBES	Integer	Number of unsubscribed users
COMPALINTS	Integer	Number of complaints
DELIVERED	Integer	Number of delivered e-mails

```
{
  "bounces": 15,
  "clicks": 115,
  "complaints": 2,
  "date": 1455708063,
  "delivered": 3880,
  "hardBounces": 5,
  "html": "http://www.mensagex.com.br/envios/1/26_preview.html",
  "id": 26,
  "lists": [{
    "id": 1,
    "name": "My Contacts"
  }, {
    "id": 2,
    "name": "Robert Contacts"
  }],
  "name": "Hello World",
  "senderEmail": "markcuban@broadcast.com",
  "senderName": "Mark Cuban",
  "sent": 3895,
  "softBounces": 10,
  "status": "SENT",
  "subject": "About hello world",
  "uniqueClicks": 80,
  "uniqueOpens": 1350,
  "unsubscribes": 2
}
```


INSERT

REQUEST

Method	Path
POST	/campaign

CAMPAING ATTRIBUTES	TYPE	REQUIRED	DESCRIPTION
DATE	Long	Yes	Schedule date in unix time
HTML	String	Yes	HTML campaign's body code
LISTS	List	Yes	Lists to be used on the campaign
NAME	String	Yes	Campaign's name
SENDEREMAIL	String	Yes	Campaign's sender e-mail
SENDERNAME	String	Yes	Campaign's sender name
SUBJECT	String	Yes	Campaign's subject

LIST

ATTRIBUTES	Type	Required	Description
ID	Integer	Yes	List's identifier

```
curl -user <any-string>:<your-api-key> \  
--request POST "https://messagex.com.br/api/campaign"  
{  
  "date": 1455708063,  
  "html": "<html><body>Hello World</body></html>",  
  "lists": [{"id": 1 }],  
  "name": "Hello World",  
  "senderEmail": "markcuban@broadcast.com",  
  "senderName": "Mark Cuban",  
  "subject": "About hello world ",  
}
```